

**NEW**

Product Data



## ORION 600 VERSATILE 50 W XENON LIGHT SOURCE

- 90-250V, 50-400 Hz UNIVERSAL POWERING
- 11-15V DC POWERING
- 12V DC OUTPUTS FOR ARGUS 600, EASY 600, LONGRANGE 600 PROBES AND MUCAM K600 CAMERA POWERING
  
- 5800° K COLOR TEMPERATURE
- REMOVABLE COUPLING BASES FOR COMPATIBILITY WITH OTHER BRANDS OF LIGHT CABLES
- LIGHT INTENSITY ADJUSTMENT
- RUGGED METALLIC CASING

## TECHNICAL FEATURES

### REFERENCE

Vocation  
Lamp  
Color temperature  
Lamp power output  
Lamp life  
Brightness tuning  
AC power supply  
DC power supply  
Dimensions  
Weight

### ORION-600

Industrial Endoscopy  
Xenon  
5800 ° K  
50 W  
2500 Hours  
Mechanical shutter  
90 - 250 V / 50-400 Hz  
11-15VDC  
340 X 160 X 80 mm  
3,350 Kg

## FRONT PANEL

ON / OFF switch  
Rotating knob for brightness adjustment  
Removable light guide cable connector base  
12V DC output for ARGUS 600, EASY 600, LONGRANGE 600 probe and MUCAM K600 camera powering

## REAR PANEL

12V power supply plug  
Mains power supply plug  
Fuses

## SAFETY FEATURES

Complies with European Directives

- Electromagnetic immunity
- Electromagnetic interference
- Electrical safety

## PRESENTATION

Full metal box

## ACCESSORIES

- Supplied  
230 V 50 Hz power supply cable  
25 cm long cable for 12V power supply output (for EFER probe) Ref : CA12-05
- Please specify when ordering  
115 V 60/400 Hz power cable  
3 M long, 12V external power supply cable  
Ref : CA12-03
- B1I (standard FORT) light cable connector base
- B2I (standard STORZ) light cable connector base
- B3I (standard OLYMPUS) light cable connector base
- B4I (standard WOLF) light cable connector base
- B5I (standard ACMI) light cable connector base
- B6I (standard VOLPI) light cable connector base